

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS ID: 31530

Issue date: 11/17/2023 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : Develon SAE 80W-90 Gear Oil

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Develon

2905 Shawnee Industrial Way

Suwanee, GA 30024

USA

T (678) 714-6000

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin sensitization, Category 1 H317 May cause an allergic skin reaction

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H317 - May cause an allergic skin reaction

Precautionary statements (GHS US) : P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - If on skin: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label). P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

No additional information available

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	CAS-No.: 64742-54-7	50 – 75	Not classified
PHOSPHORIC ACID ESTERS/AMINE SALT	CAS-No.: TRADE SECRET	1 – 5	Skin Sens. 1B, H317

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell. First aider: Pay attention to self-

protection.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. Seek medical attention if ill

effect or irritation develops.

First-aid measures after skin contact Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs:

Get medical advice/attention. Seek medical attention if ill effect or irritation develops.

First-aid measures after eye contact Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention. Rinse cautiously with water for several minutes.

First-aid measures after ingestion : Do not induce vomiting. Rinse mouth. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2).

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : vapors may cause fire/explosion if source of ignition is present. Watch out for invisible flames.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Evacuate area. Use water spray or fog for cooling exposed containers. Do not allow water to

enter the vessels, a violent reaction may occur.

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection. Other information

High temperature decomposition products are harmful by inhalation. On exposure to high

temperature, may decompose, releasing toxic gases.

US - en 11/17/2023 (Issue date) 2/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Clean up any spills as soon as possible, using an absorbent material to collect it. Prevent from

entering sewers, basements and workpits, or any place where its accumulation can be

dangerous.

6.1.1. For non-emergency personnel

Protective equipment : Avoid contact with skin, eyes and clothing. Wear recommended personal protective equipment.

Emergency procedures : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Evacuate

unnecessary personnel. Do not breathe vapors. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Wear recommended personal protective equipment. For further information refer to section 8:

"Exposure controls/personal protection".

Emergency procedures : Prevent from entering sewers, basements and workpits, or any place where its accumulation can

be dangerous.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak, if possible without risk.

Methods for cleaning up : Soak up with inert absorbent material (for example sand, sawdust, a universal binder, silica gel).

Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use. Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Weather the conditions of normal use.

: Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Ensure good ventilation of the work station. Do not breathe vapors. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Handling temperature : ≤ 140 °F

Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated

clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wear personal protective equipment. Take off immediately all contaminated clothing and wash it before reuse. Separate working clothes from town clothes.

Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Keep only in original container.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

11/17/2023 (Issue date) US - en 3/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Develon SAE 80W-90 Gear Oil		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ Contains highly refined petroleum oil	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA	5 mg/m³ Contains highly refined petroleum oil	
OSHA PEL STEL	10 mg/m³ Contains highly refined petroleum oil	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers

should be available in the immediate vicinity of any potential exposure.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:

Protective gloves. nitrile rubber gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Wear impervious rubber safety shoes. Chemical resistant apron

Respiratory protection:

In case of inadequate ventilation wear respiratory protection.

Personal protective equipment symbol(s):











SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color amber brown Odor petroleum-like odor Odor threshold No data available No data available рΗ Melting point No data available Freezing point No data available **Boiling point** No data available : 214 °C Flash point

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available Vapor pressure : No data available Relative vapor density at 20°C : No data available

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density : No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic : 138 mm²/s @ 40°C No data available Viscosity, dynamic **Explosion limits** No data available Explosive properties No data available Oxidizing properties No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal use.

10.4. Conditions to avoid

High temperature.

10.5. Incompatible materials

Acids. Oxidizing agent.

10.6. Hazardous decomposition products

fume. Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE (64742-54-7)

LD50 dermal rabbit > 5000 mg/kg Source: IUCLID

Skin corrosion/irritation : Not classified Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

11/17/2023 (Issue date) US - en 5/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard : Not classified Viscosity, kinematic : 138 mm²/s @ 40°C

Symptoms/effects after skin contact : May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Develon SAE 80W-90 Gear Oil		
LC50 - Fish [1]	> 100 mg/l	
LC50 - Other aquatic organisms [1]	> 100 mg/l	

SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE (64742-54-7)		
LC50 - Fish [1]	> 5000 mg/l	
EC50 - Crustacea [1]	> 1000 mg/l Source: IUCLID	
EC50 96h - Algae [1]	> 1000 mg/l Source: IUCLID	

12.2. Persistence and degradability

ы	AVA	O D	cΛ	_ 0	7474	w o	Λ	Gear	AΠ
12	T=Y.Y=1	ЮП	ЭΑ	· - •	I'A'		v	Gear	UП

Persistence and degradability Not rapidly degradable

PHOSPHORIC ACID ESTERS/AMINE SALT (TRADE SECRET)

Persistence and degradability Not rapidly degradable

SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE (64742-54-7)

Persistence and degradability Not rapidly degradable

12.3. Bioaccumulative potential

SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE (64742-54-7)

Partition coefficient n-octanol/water (Log Pow) 3.9 – 6 Source: IUCLID

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional waste regulation

Waste treatment methods

vaste treatment methods

Sewage disposal recommendations

Product/Packaging disposal recommendations

: Disposal must be done according to official regulations.

: Dispose of contents/container in accordance with licensed collector's sorting instructions.

: Disposal must be done according to official regulations.

: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.

Additional information : Clean up even minor leaks or spills if possible without unnecessary risk. Do not re-use empty containers.

11/17/2023 (Issue date) US - en 6/8

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ecological information : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

DOT NA No : Not regulated

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

DOT

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	J	Commercial status	Flags
PHOSPHORIC ACID ESTERS/AMINE SALT	TRADE SECRET	Not present	-	
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	64742-54-7	Present	Active	

15.2. International regulations

CANADA

SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

National regulations

SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE (64742-54-7)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

No additional information available

SECTION 16: Other information

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Full text of H-phrases		ses
	H317	May cause an allergic skin reaction

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur. NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire

conditions.



Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids,

solids and semi solids having a flash point above 200 F. (Class IIIB)

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT Physical

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal protection : B - Safety glasses, Gloves

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.