

DEVELON

Wheel Loader

DL380-7



Engine

Make	DEVELON
Model	DL08
Number of cylinders	6
Rated power, gross (hp per SAE J1995)	270.9 hp (202.0 kW) @ 1800 rpm
Rated power, net (hp per SAE J1349)	270.9 hp (202.0 kW) @ 1800 rpm
Max. torque, gross (SAE J1995)	940.0 lbf.ft. (130.0 kgf) @ 1300 rpm
Displacement	466.0 in. ³ (7.6 L)
Bore and stroke	4.3" x 5.5" (108 mm x 139 mm)
Starter	24 V, 8.6 hp (6.0 kW)
Battery	2 x 12 V, 200 AH, 1300 CCA
Alternator	24 V, 80 A
Air cleaner	Double elements

Hydraulics

Main pumps	Variable displacement axial piston pump 68.7 gpm (260.0 L/min.)
System pressure (work)	3844.0 psi (265.0 bar)
System pressure (steer)	3118.0 psi (215.0 bar)
Boom speed – up	5.9 sec
Boom speed – down	3.0 sec
Bucket speed – crowd	2.0 sec
Bucket speed – dump	1.5 sec

Travel Speeds

Travel speed – forward (4-speed)	3.7 / 7.3 / 14.5 / 22.4 mph (6.0 / 11.7 / 23.3 / 36.0 km/h)
Travel speed – forward (5-speed) (US50 and US51 packages only)	3.8 / 7.1 / 10.9 / 17.0 / 24.9 mph (6.1 / 11.5 / 17.6 / 27.4 / 40.0 km/h)
Travel speed – reverse (4-speed)	4.0 / 7.6 / 15.2 mph (6.4 / 12.3 / 24.4 km/h)
Travel speed – reverse (5-speed) (US50 and US51 packages only)	4.0 / 7.5 / 17.9 mph (6.45 / 12.1 / 28.8 km/h)
Max. grade	51% (27°)

Environment

Sound level (ISO 6395)	105 dB(A)
Cabin sound level (ISO 6396)	68 dB(A)

Refill Capacities

Fuel tank	76.9 gal. (291.0 L)
DEF tank	16.4 gal. (62.0 L)
Cooling system (radiator capacity)	11.9 gal. (45.0 L)
Engine oil	9.2 gal. (35.0 L)
Transmission	11.1 gal. (42.0 L)
Front axle	11.1 gal. (42.0 L)
Rear axles	10.6 gal. (40.0 L)
Hydraulic system	47.5 gal. (180.0 L)

All capacities are approximate values. Always refer to the machine's OM for exact refill levels. Check the dipstick, level eye, level plug, etc., to achieve the correct level.

Hydraulic Cylinders

Steering (2) bore x rod diameter x stroke	3.5" x 2.0" x 17.7" (90 mm x 50 mm x 450 mm)
Lift arm (2) bore x rod diameter x stroke	5.9" x 3.7" x 31.5" (150 mm x 95 mm x 800 mm)
Bucket (1) bore x rod diameter x stroke	7.1" x 4.1" x 21.1" (180 mm x 105 mm x 535 mm)

The piston rods and cylinder bodies are made of high-strength steel. A shock-absorbing mechanism is fitted in at the base and rod end of the lift and bucket cylinders and the rod end of the steering cylinders to ensure shock-free operation and extended piston life.



NOTE: Where applicable, dimensions are in accordance with Society of Automotive Engineers (SAE) and ISO standards. Specifications and design are subject to change without notice. All dimensions are given for DEVELON wheel loaders equipped with standard tires. Pictures of DEVELON wheel loaders may show other than standard equipment. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Rounding may impact specifications DEVELON construction equipment is manufactured with a Quality Management System that is in compliance with ISO 9001:2008.

Dimensions

		Standard Arm	High-Lift
Bucket capacity, heaped ISO/SAE		5.1 yd³ (3.9 m³)	
Bucket width	A	10' 2.4" (3110 mm)	
Max. hinge pin height	B	13' 8.2" (4170 mm)	15' 4.6" (4690 mm)
Dump height (45°) – fully raised	C	9' 11.7" (3040 mm)	11' 8.2" (3560 mm)
Dump reach (45°) – fully raised	D	4' 0.0" (1220 mm)	4' 8.1" (1425 mm)
Digging depth	E	3.3" (85 mm)	5.7" (145 mm)
Overall height, ROPS cabin	F	11' 6.2" (3511 mm)	
Overall length	G	27' 2.6" (8296 mm)	28' 7.9" (8736 mm)
Wheel base	H	10' 9.9" (3300 mm)	
Tread width	I	7' 0.6" (2150 mm)	
Ground clearance	J	1' 3.7" (400 mm)	
Max. tilt angle on ground*		44°	45°
Max. tilt angle at carry position	K	48°	51°
Max. tilt angle at fully raised	L	64°	63°
Max. dump angle at fully raised	M	45°	
Max. steering angle	N	40°	
External turning radius, bucket edge	O	21' 10.0" (6655 mm)	22' 10.0" (6960 mm)
External turning radius, outside tire	P	19' 6.6" (5960 mm)	
Tire size		23.5 R25 (23.5 R25)	
Operating weight		45022 lb. (20422 kg)	45728 lb. (20742 kg)
Static tipping load (straight)		36074 lb. (16363 kg)	26733 lb. (12126 kg)
Static tipping load (at full turn)		31855 lb. (14449 kg)	23609 lb. (10709 kg)
Breakout force		36342 lbf. (175.0 kN)	38442 lbf. (171.0 kN)

*Not shown on diagram

Front Lift Arm Configuration
Standard: U510, U511, U550, U551
High-Lift: U520, U521



Standard & Optional Equipment

Standard Base Package, US10

■ Standard ● Optional

Engine

Emissions (EPA), T4f	■
High-pressure common-rail (HPCR)	■
Turbo, variable geometry (VGT)	■
Cooled exhaust gas recirculation (CEGR)	■
Diesel oxidation catalyst (DOC)	■
Selective catalytic reduction (SCR)	■
Diesel exhaust fluid (DEF)	■
Fuel filter with water separator	■
Coolant recovery tank	■
Dual element dry-type air filter with evacuator	■
Precleaner	■
Electronic engine control (ECU)	■
Auto idle (working to standby)	■
Auto shutdown (time adjustable)	■
Overheat & low oil pressure engine protection	■
Cooling fan – radiator, variable speed	■
Cooling fan – radiator, automatic reversible	■
Remote drain port – engine oil	■
Block heater (110 V)	■

Hydraulic

Variable displacement axial piston pump	■
Closed-center system	■
Main control valves, pilot	■
Remote test ports	■
Remote drain port, hydraulic oil	■
Auxiliary hydraulics (3rd valve)	■
Automatic boom/lift kick-out, adjustable (in cab)	■
Automatic return-to-dig position, adjustable	■
Boom float	■
Ride control	■

Electrical

System voltage – 24 V	■
Alternator – 24 V, 80 A	■
2 x 12 V batteries, 200 AH reserve capacity, 1300 CCA	■
Blade-type fuse panel	■
Main circuit breaker	■
Lights, work (LED): front (2), rear (2)	■
Lights, work (LED): front (4), rear (4)	●
Lights, work (LED): front (6), rear (6)	●
Lights, headlights (halogen): hi/lo beams (2)	■
Lights, stop, tail & direction indicators	■
Horn	■
Rotating beacon	■
Hour meter	■
Engine restart prevention system	■
Rearview camera	■
Laptop service port	■
Self-diagnostics system	■

Cabin

Steel, all-weather & sound-suppressed	■
ROPS (ISO 3471)	■
FOPS (ISO 3449)	■
Front window with wiper/washer	■
Rear window with wiper	■
Tinted safety glass	■
Visor, retractable	■
Adjustable sliding side door window	■
Defrost, front window	■
Lockable doors	■
Seat	■
- Air-suspension	
- 3" (76 mm) seat belt	
- Adjustable height & recline	
- Adjustable fore/aft	
- Adjustable armrests	
Control stands	■
- Height adjustable	
- Fore/aft adjustable	
Storage for operator's manuals	■
Mirror, interior rearview (1)	■
Mirrors, exterior (2), heated	■
Mirrors, exterior (2), heated (electronic adjustable)	●
Fully automatic HVAC with ambient temperature sensor	■
Smart Touch display	■
- 8" touch-enabled	
- Adjustable height & angle	
Transparent Bucket	■
- Multi-camera system & controller	
- In-cab display	
AM/FM stereo with Bluetooth®	■
Speakers (2)	■
Antenna, roof-mounted	■
Emergency breakout tool	■
Power socket, 12 V	■
Power socket, USB	■
Cup holder	■
Interior light	■
Coat hanger	■

Controls

Adjustable steering column	■
- Tilting	
- Telescoping	
Emergency secondary steering	●
Throttle pedal (accelerator)	■
Brake pedal, right	■
Brake pedal, left	■
Brake pedal transmission kick-out	■
Gear selector (FNR)	■
Joystick control	■
Fingertip control (3-lever)	●
Switches, console-mounted	■
- Starter (button)	
- Parking brake	
- Pilot cutoff	
- Transmission cutoff	
- Work light	
- Reversible cooling fan	
Emergency stop switch	■
Power mode (P, S, E)	■
Transmission mode (manual / auto 1-4 / auto 2-4)	■
Wiper control panel	■
Audio control panel	■

Display Monitor & Warnings

Buzzer		
- Engine oil pressure		■
- Coolant temperature		
- Transmission overheat		
Gauges		
- Fuel level	- ECO	
- DEF level	- Smart guidance system	
- Engine coolant temperature	- Digital clock	
- Transmission oil temperature	- Trip meter	■
- Engine rpm	- Hour meter	
- Speedometer	- Total operation time	
- Transmission gear indicator	- Fuel consumption	
- Battery voltage		
Warning & indicator lights		
- Seat belt	- Emergency steering	
- Error code	- Hydraulic oil temperature	
- SCR warning	- Hydraulic charge	
- Check engine	- pressure warning	
- Engine oil pressure	- Hydraulic pilot filter	
- Engine pre-heat engaged	- Hydraulic return filter	
- Radiator coolant level	- Transmission mode	
& temperature	- Transmission warning	■
- Air filter	- Transmission lock-up	
- Fuel level	- Transmission oil temp	
- DEF level – low	- Transmission gear indicator	
- Water in fuel	- Brake fluid pressure warning	
- Battery charge	- Reverse fan indicator	
- Direction signal	- Mirror heat indicator	
- Lights (high, main, work, beacon)	- Parking brake indicator	
Back-up alarm		■
Situation Awareness Technology (SAT)		■
Scale system, integrated smart scale		●
Around view monitor (AVM)		●

Frame & Driveline

Z-bar lift arm	■
Z-bar lift arm, high-lift	●
Steering cylinders, double-acting (2)	■
Transmission – 4F/3R speed	■
- Full automatic – power shift	
- Torque converter	
Transmission – 5F/3R speed	●
- Automatic – power shift	
- Torque converter lock-up clutch	
Differentials	■
- Limited slip front/rear	
Differentials	●
- Hydraulic locking front	
- Open rear	
Hydraulic power steering	■
Outboard planetary axles	■
Fixed front axle	■
Oscillating rear axle	■
Spring-applied hydraulic release brake	■
Sealed, self-adjusting brakes	■
Tires, 20.5R25 L3 radial	■
Outboard brakes	■

Other

Centralized lubrication	■
Air-compressor	●
Handrails, entrance & service steps	■
Handrails, roof-mounted	■
Skid-resistant entrance steps	■
Skid-resistant service platforms	■
Drawbar & pin	■
Wheel chocks	■
Rear fender, full	●
Additional counterweight*	●
Manuals	■
- Operation & Maintenance	
- AEM Safety Manual	
MY DEVELON (telematics)	■
Vandalism protection	■
- Lockable panels	
- Lockable fluid fill points	
- Anti-theft protection (password)	

*Standard on high-lift models

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual DEVELON equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors. Pictures of DEVELON units may show other than standard equipment.

Powered by Innovation

DEVELON

A brand of HD Hyundai Infracore.

na.develon-ce.com/dl380-7

DL380-7 Wheel Loader Spec Sheet
Printed in the U.S.A.
25903_006_D092225

©2025 HD Hyundai Infracore. All rights reserved.